

1. PRODUCT & COMPANY IDENTIFICATION

• Product Detail:

Product name: BONDPLAST Physical form: Powder Odour: Odourless Colour: Grey CAS No.:

• Company Details:

Manufacturer: Highbond Coatings Pvt Ltd Address: Sr. No. 70/2B/1, Flat No 101 & 102, Purushottam Villa, Vadgaon Bk,

Pune – 411041 **Tel:** +91 9370953995

Email: info@highbondcoatings.com

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture GHS Classification:

Acute toxicity, Inhalative, Category 4 (H332)

Skin irritation, Category 2 (H315)

Eye irritation, Category 2 (H319)

Sensitization of the respiratory airways, Category 1 (H334) Sensitization of the skin, Category 1 (H317) Carcinogenicity,

Category 2 (H351)

Specific target organ toxicity (single exposure),

Category 3 (H335)

Specific target organ toxicity (repeated exposure), Category 2

(H373)

2.2 Label elements GHS-Labelling







Signal word Danger

Uncured product

Hazard statements:

H226 Flammable liquid and vapor H315

Causes skin irritation.

H319 Causes serious eye irritation. H401

Toxic to aquatic life

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

3. COMPOSITION/HAZARDOUS COMPONENTS

Chemical description: Mixtures

Chemical Name	CAS No.	WT%
Diphenyl methane diisocyanate- prepolymer	Proprietary	10 - 30%
Phthalate ester	68515-48-0	10 - 30 %
Calcium Carbonate	147-34-1	25 - 35%
Magnesium Silicate	14807-96-6	10 - 20%
2,2'-Dimorpholinyldiethyl ether	6425-39-4	<1%
Dimethyl benzene	1330-20-7	10 - 20%

4. FIRST-AID MEASURES

Take off all contaminated clothing immediately.

In case of inhalation: Supply fresh air and to be sure call for a doctor.

In case of ingestion: Do not induce vomiting. Seek medical advice immediately.

In case of skin contact: Wipe with paper towel and immediately clean with water and soap. **In case of eyes contact:** Immediately flush with water, seek medical advice if necessary.

Indication of any immediate attention and special treatment needed:

No further relevant information available.

5. FIRE FIGHTING MEASURES

- Suitable extinguishing media: Water spray, dry extinguishing media, carbon dioxide or universal foams Contaminated extinguishing water must be disposed of in accordance with local regulations
- Unsuitable extinguishing media: High volume water jet
- **Hazardous decomposition:** Carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides and formaldehyde



6. ACCIDENTAL RELEASE MEASURES

- **Small spills:** Slippery when spilt. Avoid accidents, clean up immediately. Wipe up with rag or absorbent paper.
- Large spills: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers or drums for disposal. Wash area down with excess water. Cured material can only be removed by cutting or abrasion.

7. HANDLING AND STORAGE

- **Handling:** Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.
- **Protection against fire/ explosion:** General rules of fire prevention should be observed.
- **Storage:** Keep container tightly closed and dry.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Ingredients with limited values to be controlled:Not indicated.Local exhaust:RecommendedGeneral ventilation:Recommended

Hand protection:Suitable protective gloves. **Eye protection:**Safety/ protective glasses.

Flammability: Combustible

Note: Until more data is known, exposure levels should be maintained as low as achievable.

9. PHYSICAL AND CHEMICAL PROPERTIES

TEST	RESULTS	
Colour	Greyish Granular Powder	
Dry Density	1700 kg/m"	
Water Retentivity	Min. 95%	
Pot Life	1-1.5 Hrs	
Initial/Final Setting Time	30/600 Mins	
Compressive Strength	8.5-12.5 MPa	
Flexural Strength	1.8 -2.0 MPa	
Pull Off Adhesion Strength	0.3 - 0.4 MPa	



10. STABILITY AND REACTIVITY

Chemical stability: Stable
Incompatibility (material to be avoid): None known.
Conditions to be avoid: None known.
Dangerous reactions: None known.
Dangerous products of decomposition: None known.

11.TOXICOLOGICAL INFORMATION

Acute toxicity: Not determined

Primary irritant effect,

On the skin: Irritant for skin and mucous membranes.

On the eye: Irritant effect

Sensitization:Sensitization possible by inhalation.Additional ToxicologicalUntil more data is known, exposure levels

information: should be

Information on toxicological effects

Information on toxicological effects Acute

Toxicity

LD/LC50 values relevant for

classification: LD50 4300 mg/kg (rat) LD50 2000 mg/kg

1330-20-7 xylene (rabbit) ·

Oral DermalIrritating. IrritatingPrimary irritant effect: onNot classified

the skin: on the eve:

Sensitization:

12.ECOLOGICAL INFORMATION

Toxicity

Acquatic toxicity information available.

Persistence and degradability: No further relevant information available **Bioaccumulative potential:** No further relevant information available

Mobility in soil: No further relevant information available

General Notes:

Water hazard Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities

Results of PBT and vPvB assessment: Non applicable
Other adverse effects: Avoid release to the environment No

further relevant information available



13. REGULATORY INFORMATION

Safety, health and environmental regulation/legislation specific for the substance or mixture

The mixture classification is according to CLP Regulation 1272/2008/EC ·

Labelling according to Regulation (EC) No 1272/2008 Label elements in Section 2.2 **National regulations:**

Other regulations, limitations and prohibitive regulations Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

14. OTHER INFORMATION

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

Highbond Coatings Pvt Ltd

Sr. No. 70/2B/1, Flat No 101 & 102, Purushottam Villa, Vadgaon Bk,

Pune - 411041 **Tel:** +91 9370953995

Mail: info@highbondcoatings.com

