

# 1. PRODUCT & COMPANY IDENTIFICATION

• Product Detail:

**Product name:** MASTERBOND **Physical form:** Thick paste

Odor: None Colour: Green CAS No.:

• Company Details:

Manufacturer: Highbond Coatings Pvt Ltd Address: Sr. No. 70/2B/1, Flat No 101 & 102, Purushottam Villa, Vadgaon Bk,

Purushottam Villa, Vadgaon . Pune – 411041

**Tel:** +91 9370953995

Email: info@highbondcoatings.com

# 2. HAZARDS IDENTIFICATION

# Classification of the substance or mixture GHS $\,$

**Classification:** 

Acute toxicity, Inhalative, Category 4 (H332)

Skin irritation, Category 2 (H315)

Eye irritation, Category 2 (H319)

Sensitization of the respiratory airways, Category 1 (H334)  $\,$ 

Sensitization of the skin, Category 1 (H317) Carcinogenicity,

Category 2 (H351)

Specific target organ toxicity (single exposure),

Category 3 (H335)

Specific target organ toxicity (repeated exposure), Category 2

(H373)

2.2 Label elements GHS-Labelling







Signal word Danger

# **Uncured product**

# Hazard statements:

H315 Causes skin irritation.

H318 - Causes serious eye damage

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.

# 3. COMPOSITION/ HAZARDOUS COMPONENTS

**Chemical description:** Mixtures

# **COMPOSITION**

**MASTERBOND** -It is a green aqueous dispersion of vinyl acetate copolymer with mineral filling materials.

#### 4. FIRST-AID MEASURES

Take off all contaminated clothing immediately.

**In case of inhalation:** Supply fresh air and to be sure call for a doctor.

**In case of ingestion:** Do not induce vomiting. Seek medical advice immediately.

**In case of skin contact:** Wipe with paper towel and immediately clean with water and soap. **In case of eyes contact:** Immediately flush with water, seek medical advice if necessary.

Indication of any immediate attention and special treatment needed:

No further relevant information available.

# 5. FIRE FIGHTING MEASURES

- Suitable extinguishing media: Water spray, dry extinguishing media, carbon dioxide or universal foams Contaminated extinguishing water must be disposed of in accordance with local regulations
- Unsuitable extinguishing media: High volume water jet
- **Hazardous decomposition:** Carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides and formaldehyde.

# 6. ACCIDENTAL RELEASE MEASURES

- **Small spills:** Slippery when spilt. Avoid accidents, clean up immediately. Wipe up with rag or absorbent paper.
- Large spills: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers or drums for disposal. Wash area down with excess water. Cured material can only be removed by cutting or abrasion.



#### 7. HANDLING AND STORAGE

- **Handling:** Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.
- Protection against fire/explosion: General rules of fire prevention should be observed.
- **Storage:** Keep container tightly closed and dry.

# 8. EXPOSURE CONTROL/ PERSONAL PROTECTION

**Ingredients with limited values to be controlled:** Not indicated.

**Local exhaust:** Recommended **General ventilation:** Recommended

**Hand protection:** Suitable protective gloves. **Eye protection:** Safety/ protective glasses.

Flammability: Combustible

**Note:** Until more data is known, exposure levels should be maintained as low as achievable.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

| PROPERTIES            | RESULTS              |
|-----------------------|----------------------|
| Appearance            | Thick paste          |
| Color                 | Green                |
| Specific Gravity      | 1.45 ± 0.05          |
| Solubility with Water | Soluble              |
| Setting Time          | 24 Hrs.              |
| Bonding Strength      | >1mpa                |
| рН                    | 9±1                  |
| Water Resistance      | Excellent            |
| Pull out adhesion     | 1 N/mm2              |
| Coverage              | 50 Sq. ft/Kg         |
| Chemical Composition  | Polymer based liquid |
| Drying Type           | Air Drying           |

# 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable

Incompatibility (material to be avoid): None known.

Conditions to be avoid: None known.

Dangerous reactions: None known.

Dangerous products of decomposition: None known.



# 11. TOXICOLOGICAL INFORMATION

**Acute toxicity:** Not determined

Primary irritant effect,

**On the skin:** Irritant for skin and mucous membranes.

On the eye: Irritant effect

Sensitization:Sensitization possible by inhalation.Additional ToxicologicalUntil more data is known, exposure levels

**information:** should be

Information on toxicological effects

Information on toxicological effects Acute

**Toxicity** 

LD/LC50 values relevant for

classification: 1330-20-7 xylene

**330-20-7 xylene** LD50 4300 mg/kg (rat) LD50 2000 mg/kg

Oral Dermal (rabbit) ·

**Primary irritant effect:**on the skin: on the eye: Sensitization:
Not classified

# 12. ECOLOGICAL INFORMATION

**Toxicity** 

Aquatic toxicity information available.

**Persistence and degradability:** No further relevant information available **Bio-accumulative potential:** No further relevant information available

Mobility in soil: No further relevant information available

**General Notes:** 

Water hazard Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities

Results of PBT and vPvB assessment: Non applicable

Other adverse effects: Avoid release to the environment No

further relevant information available.

# 13. DISPOSAL CONSIDERATIONS

Dispose at an authorized landfill site in accordance with the Waste Management Licensing Regulations 1994. Packaging should be emptied completely and sent preferably for recycling or processing.



#### 14. REGULATORY INFORMATION

Safety, health and environmental regulation/legislation specific for the substance or mixture

The mixture classification is according to CLP Regulation 1272/2008/EC ·

**Labelling according to Regulation (EC) No 1272/2008** Label elements in Section 2.2 **National regulations:** 

Other regulations, limitations and prohibitive regulations Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# 15. OTHER INFORMATION

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

**End of Safety Data Sheet** 

# **Highbond Coatings Pvt Ltd**

Sr. No. 70/2B/1, Flat No 101 & 102, Purushottam Villa, Vadgaon Bk, Pune – 411041

**Tel:** +91 9370953995

Mail: info@highbondcoatings.com

