

1. PRODUCT & COMPANY IDENTIFICATION

- **Product Detail:**

Product name: SHUTTERING OIL

Physical form: liquid

Odour: Mild

Colour: Dark brown to amber

CAS No.:

- **Company Details:**

Manufacturer: Highbond Coatings Pvt Ltd

Address: Sr. No. 70/2B/1, Flat No 101 & 102,
Purushottam Villa, Vadgaon Bk, Pune – 411041

Tel: +91 9370953995

Email: info@highbondcoatings.com

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification:

Acute toxicity, Inhalative,

Category 4 (H332)

Skin irritation, Category 2 (H315)

Eye irritation, Category 2 (H319)

Sensitization of the respiratory airways, Category 1 (H334)

Sensitization of the skin, Category 1 (H317)

Carcinogenicity, Category 2 (H351)

Specific target organ toxicity (single exposure),

Category 3 (H335)

Specific target organ toxicity (repeated exposure),

Category 2 (H373)

2.2 Label elements

GHS-Labeling



Signal word **Danger**

Uncured product

Hazard statements:

H315 Causes skin irritation.

H318 - Causes serious eye damage

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

3. COMPOSITION/ HAZARDOUS COMPONENTS

EC Classifications: Not classified as hazardous. No other hazardous substance present.

4. FIRST-AID MEASURES

Take off all contaminated clothing immediately.

In case of inhalation: Supply fresh air and to be sure call for a doctor.

In case of ingestion: Do not induce vomiting. Seek medical advice immediately.

In case of skin contact: Wipe with paper towel and immediately clean with water and soap.

In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

Indication of any immediate attention and special treatment needed:

No further relevant information available.

5. FIRE FIGHTING MEASURES

Skin irritant may be caused by direct and prolonged contact. Wash contacted areas thoroughly

No special requirement for fire-fighting. Chemical burns easily when ignited.

6. ACCIDENTAL RELEASE MEASURES

Contain and collect with absorbent material. Keep out of drains and sewers.

7. HANDLING AND STORAGE

- **Handling:** Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.
- **Protection against fire/ explosion:** General rules of fire prevention should be observed.
- **Storage:** Keep container tightly closed and dry.

8. EXPOSURE CONTROL/ PERSONAL PROTECTION

Ingredients with limited values to be controlled: Not indicated.

Local exhaust: Recommended

General ventilation: Recommended

Hand protection: Suitable protective gloves.

Eye protection: Safety/ protective glasses.

Note: Until more data is known, exposure levels should be maintained as low as achievable.

9. PHYSICAL AND CHEMICAL PROPERTIES

PROPERTIES	RESULTS
Appearance	Dark Brown to amber
Physical State	Liquid
Specific Gravity	0.96 at 27°C
Shelf Life	12 Months

10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions.

11. TOXICOLOGICAL INFORMATION

N/A

12. ECOLOGICAL INFORMATION

This product is not classified as dangerous to the environment according to the EC directive 93/21/EEC.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all local and governmental regulations

Unused Product: Dispose of through an authorized waste contractor to a licensed site.

Used/Contaminated Product: As for Unused product.

Packaging: May be steam cleaned and recycled.

14. OTHER INFORMATION

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

Highbond Coatings Pvt Ltd

Sr. No. 70/2B/1, Flat No 101 & 102,
Purushottam Villa, Vadgaon Bk,
Pune - 411041

Tel: +91 9370953995

Mail: info@highbondcoatings.com