

1. PRODUCT & COMPANY IDENTIFICATION

- **Product Detail:**

Product name: WHITEBOND WB PRO

Physical form: Viscous Liquid

Odour:

Colour: White

CAS No.:

- **Company Details:**

Manufacturer: Highbond Coatings Pvt Ltd

Address: Sr. No. 70/2B/1, Flat No 101 & 102,
Purushottam Villa, Vadgaon Bk,
Pune – 411041

Tel: +91 9370953995

Email: info@highbondcoatings.com

2. Hazards Identification

Classification of the substance or mixture

GHS Classification:

Acute toxicity, Inhalative,

Category 4 (H332)

Skin irritation, Category 2 (H315)

Eye irritation, Category 2 (H319)

Sensitization of the respiratory airways, Category 1 (H334)

Sensitization of the skin, Category 1 (H317)

Carcinogenicity, Category 2 (H351)

Specific target organ toxicity (single exposure),

Category 3 (H335)

Specific target organ toxicity (repeated exposure),

Category 2 (H373)

2.2 Label elements

GHS-Labeling



Signal word **Danger**

Uncured product

Hazard statements:

H315 Causes skin irritation.

H318 - Causes serious eye damage

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

3. COMPOSITION/ HAZARDOUS COMPONENTS

Chemical description: Mixtures

Chemical Name	CAS No.	WT%
Calcium carbonate	1317-65-3	30-40
Titanium Dioxide	13463-67-7	0 – 10
Ethylene Glycol	107-21-1	0 - 2

4. FIRST-AID MEASURES

Take off all contaminated clothing immediately.

In case of inhalation: Supply fresh air and to be sure call for a doctor.

In case of ingestion: Do not induce vomiting. Seek medical advice immediately.

In case of skin contact: Wipe with paper towel and immediately clean with water and soap.

In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

Indication of any immediate attention and special treatment needed: No further relevant information available.

5. FIRE FIGHTING MEASURES

- **Suitable extinguishing media:** Water spray, dry extinguishing media, carbon dioxide or universal foams Contaminated extinguishing water must be disposed of in accordance with local regulations
- **Unsuitable extinguishing media:** High volume water jet
- **Hazardous decomposition:** Carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides and formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

- **Small spills:** Slippery when spilt. Avoid accidents, clean up immediately. Wipe up with rag or absorbent paper.
- **Large spills:** Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers or drums for disposal. Wash area down with excess water. Cured material can only be removed by cutting or abrasion.

7. HANDLING AND STORAGE

- **Handling:** Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.
- **Protection against fire/ explosion:** General rules of fire prevention should be observed.
- **Storage:** Keep container tightly closed and dry.

8. EXPOSURE CONTROL/ PERSONAL PROTECTION

Ingredients with limited values to be controlled: Not indicated.

Local exhaust: Recommended

General ventilation: Recommended

Hand protection: Suitable protective gloves.

Eye protection: Safety/ protective glasses.

Flammability: Combustible

Note: Until more data is known, exposure levels should be maintained as low as achievable.

9. PHYSICAL AND CHEMICAL PROPERTIES

TECHNICAL DATA	
Appearance	Viscous Liquid
Nature	Single Component
Method of Application	Brush / Roller
Solid Content	65± 2% (ASTM – D 1644-03)
Colour	White, Grey
Viscosity (Spindle No: 4/7; RPM: 10/20@25° C	50000 to 70000 CPS (thixotropic)
Specific Gravity	1.30 + 0.10 (ASTM – D 1475 03)
Curing Time	Approx.48 hours (at 20°C, 50% RH) (ASTM C 4125)
Drying Time @ 25° C.	Approx. 2 hours (ASTM D 1640-03)
Hardness Shore A	55 ± 5 (ASTM – D 2240-05)
Resistance to Temperature	Approx. -30 °C to +100 °C
Elongation Break	> 300 % (ASTM – D 2370-98)
Tensile Strength N/mm ²	2.70 (ASTM – D 412-98a)
Water Permeability	Almost zero
UV Resistance	10,000 hrs No deterioration or color fade. (ASTM D 822)
Flash Point	Non-flammable
Chemical Resistance	Good
Insulation Properties	Good
Adhesion Strength N/mm ²	66.00 (ASTM – D 903-98)
Pull Off Test N/mm ²	2.704 (BS 1881:part 207:1992)
Water Vapor Transmission g/h-m ²	0.97 (ASTM E 96-095)

10. STABILITY AND REACTIVITY

Chemical stability: Stable

Incompatibility (material to be avoid): None known.

Conditions to be avoid: None known.

Dangerous reactions: None known.

Dangerous products of decomposition: None known.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:	Not determined
Primary irritant effect,	
On the skin:	Irritant for skin and mucous membranes.
On the eye:	Irritant effect
Sensitization:	Sensitization possible by inhalation.
Additional Toxicological information:	Until more data is known, exposure levels should be Information on toxicological effects
Information on toxicological effects	
Acute Toxicity	
LD/LC50 values relevant for classification:	
1330-20-7 xylene	LD50 4300 mg/kg (rat) LD50 2000 mg/kg
Oral Dermal	(rabbit) ·
Primary irritant effect:	Irritating. Irritating
on the skin: on the eye:	Not classified
Sensitization:	

12. ECOLOGICAL INFORMATION

Toxicity
Acquatic toxicity information available.
Persistence and degradability: No further relevant information available
Bioaccumulative potential: No further relevant information available
Mobility in soil: No further relevant information available
General Notes:
Water hazard Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities
Results of PBT and vPvB assessment: Non applicable.
Other adverse effects: Avoid release to the environment.

No further relevant information available.

13. REGULATORY INFORMATION

Safety, health and environmental regulation/legislation specific for the substance or mixture

The mixture classification is according to CLP Regulation 1272/2008/EC ·

Labelling according to Regulation (EC) No 1272/2008 Label elements in Section 2.2

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

Chemical safety assessment: A Chemical Safety Assessment has not been carried out

14. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

End of Safety Data Sheet



Highbond Coatings Pvt Ltd

Sr. No. 70/2B/1, Flat No 101 & 102,
Purushottam Villa, Vadgaon Bk,
Pune – 411041

Tel : +91 9370953995

Mail : info@highbondcoatings.com